# Capstone<sup>™</sup> FS-30

Fluorosurfactant

# **Technical Information**

# Description

Capstone<sup>™</sup> FS-30 is a general-purpose, water-soluble, ethoxylated nonionic fluorosurfactant that modifies surface energies at very low concentrations. FS-30 does not contain any intentionally-added VOC or APEO compounds, and is compatible with additives and resins of any ionic class. FS-30 is stable in acidic, basic, brine, and hard water environments.

Due to its good stability across a broad pH range, FS-30 is an ideal wetting and leveling agent for many aqueous applications. It is effective as a plating bath aid by reducing drag-out from bath applications. Additionally, it can be used in coatings to reduce surface defects and lower surface tension in many types of cleaning formulations.

# Applications

# Water-Based Floor Care (Finishes, Waxes, and Polishes)

- Excellent wetting and leveling, reduced orange peel effect, extends open time
- Good re-wet characteristics in multi-coat applications
- Reduces cratering and provides faster spreading
- Compatible with hydrocarbon surfactants
- Suggested use rates are 0.01–0.05% active ingredient (A.I.)

# **Concentrated Cleaning Solutions**

- Reduces surface tension and provides excellent wetting to achieve cleanability
- Provides improved wetting and penetration, especially with difficult to wet soils
- Suggested use rates are 0.01-0.1% A.I.

## Aqueous-Based Paints and Inks

- Excellent wetting and leveling, reduced orange peel effect, extends open time
- Suggested use rates are 0.01–0.1% A.I. in aqueousbased paints


# **Typical Properties**

Appearance	Clear yellow liquid
рН	6-8.5
Specific Gravity	1.1
Stability	Freeze-thaw stable. Stable in brine and aggressive media. Mix well before use.
Composition	25% solids in water
Shelf Life	5 years
Flash Point	Does not flash



#### Performance

Surface Tension



#### Foaming

Moderate to high foamer

## Ross-Miles Foam Volume (mL) at 25 °C (77 °F) at 0.1% Active Ingredient (A.I.)

	Initial	5 min	10 min	15 min
DI Water	159	159	159	159
10% NaCl	115	112	110	109

#### Capstone<sup>®</sup> Repellents and Surfactants

- Deliver maximum performance
- Regulatory and stewardship information is available upon request
- Are listed on TSCA inventory

#### **Package Sizes**

Drum-400 lb (181.6 kg), Pail-40 lb (18.16 kg), Nalgene bottle-8 lb (3.632 kg)

For questions regarding technical data, commercial supply, and sampling:

#### **Chemours Advanced Performance Materials**

#### **Technical Inquiries**

Asia Pacific	+86.400.671.6789
Europe	+41.22.719.1537
Latin America	+55.08.0011.0728
North America	+1.866.828.7009

#### Regional Technical Customer Service Center, Americas

The Chemours Company Chemours Discovery Hub 201 Discovery Boulevard Newark, DE 19713 USA +1.866.828.7009

#### For more information, visit www.chemours.com/capstone

CAUTION: Do not use or resell Chemours" materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative. For medical emergencies, spills, or other critical situations, call (866) 595-1473 within the United States. For those outside of the United States, call (302) 773-2000.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

© 2021 The Chemours Company FC, LLC. Capstone" is a trademark of The Chemours Company FC, LLC. Chemours" and the Chemours Logo are trademarks of The Chemours Company.

Replaces: K-23711-2 C-10942 (4/21)